



Schall-Ex® DUO L-15 WS
Retractable door seal



- > Adapts perfectly to any floor condition due to 3-spring mechanism
- > Abrasive surface reduced by up to 83%



Rainstop® L-24/20 WS
Retractable door seal



Driving rain seal for barrier-free external doors



Seals

6



- > Area of application: For soundproof doors (DIN 4109), for smoke control doors in compliance with EN 1634-3, for fire resistant doors in compliance with EN 1634-1
- > Material: Carrier: Aluminium, sealing profile: Silicone, self-extinguishing
- > Finish: Carrier: Bright, sealing profile: Grey
- > Version: Double-sided release
- > Sound proofing value: 51 dB with 6 mm floor gap, 50 dB with 7 mm floor gap
- > Sealing height: ≤12 mm
- > Installation: For full mortice fitting with mounting brackets (also fixed sizes), lengths from 833 mm can be shortened by ≤125 mm (also fixed sizes)
- > Installation dim.: Groove: 15 x 30 mm
- > Mounting: For DIN left and DIN right hand use

Supplied with

- 1 retractable door seal
- 2 release plates with screws

Length mm	Cat. No.
708	950.05.501
833	950.05.502
958	950.05.503
1083	950.05.504
1208	950.05.505

Order reference

Fixed lengths available on request.

Semi-circular threshold trim	▶ AH 6.21
Flat threshold trim	▶ AH 6.22

- > Area of application: For inward and outward opening doors
- > Material: Carrier: Aluminium, sealing profile: Silicone, self-extinguishing
- > Finish: Carrier: Silver anodized, sealing profile: Grey
- > Version: Single-side release
- > Sound proofing value: 52 dB with 7 mm floor gap
- > Sealing height: ≤16 mm
- > Installation: For full mortice fitting with fixing brackets (also fixed sizes), lengths from 801 mm can be shortened on both sides, adjustable without tools
- > Installation dim: Groove: 24 x 20 mm
- > Mounting: For DIN left and right hand use

Supplied with

- 1 retractable door seal
- 1 release plate with screw
- 2 mounting brackets with screws
- 2 corner seals

Length mm	Cat. No.
750	950.05.593
900	950.05.594
1050	950.05.595
1200	950.05.596
1250	950.05.597

Packing: 1 piece

Order reference

Fixed lengths available on request.

Optionally available: Prepared for shoot bolt (Ø 10 mm).

DGH-B-INT 2019, HDE-en, 12/18; Dimensional data not binding. We reserve the right to alter specifications without notice.