

→ Set

	Version	Supplied with	Cat. No.
For 1 door	With clip-in door stopper	2 running gears 2 door stoppers with clip-in door stopper 1 inspection support 1 guide 1 mounting aid	402.33.016
	With soft and self closing mechanism on both sides, 20 kg	2 running gears with soft and self closing mechanism 2 door stoppers for soft and self closing mechanism 1 guide 1 mounting aid	402.33.017
For 2 doors	With clip-in door stopper	4 running gears 4 door stoppers with clip-in door stopper 1 door follower 2 inspection supports 2 guides 1 mounting aid	402.33.018
	With soft and self closing mechanism on one side, 20 kg	4 running gears (2 with soft and self closing mechanism) 4 door stoppers (2 with clip-in door stopper, 2 for soft and self closing mechanism) 1 door follower 2 guides 1 mounting aid	402.33.019
	With soft and self closing mechanism on both sides, 20 kg	4 running gears with soft and self closing mechanism 4 door stoppers for soft and self closing mechanism 1 door follower 2 guides 1 mounting aid	402.33.020

Packing: 1 set

Order reference







Please order running and guide tracks separately.

For cabinets with 3 doors, please order following sets: 1 set for 1 door and 1 set for 2 doors.

Note

The pitch length of the running gears must be min. 245 mm with soft closing mechanism on one side and min. 425 mm with soft closing mechanism on both sides. Inspection support cannot be used in combination with running gear with soft and self closing mechanism.

→ Tracks and accessories

		Cabinet top panel thickness mm	Material	Finish/colour	Length m	Cat. No.
Single top running track, for press fitting and glue fixing into groove 16 mm or for screw fixing with countersunk head screws 3 mm		Glue fixing: Min. 19; screw fixing: Min. 30	Aluminium	Bright, visible areas grooved	2.5	402.33.642
					3.5	402.33.643
Double top running track, for press fitting and glue fixing into groove 16 mm or for screw fixing with countersunk head screws 3.5 mm		Glue fixing: Min. 19; screw fixing: Min. 30	Aluminium	Bright, visible areas grooved	2.5	402.33.652
					3.5	402.33.653
Single top running track, for screw fixing with countersunk head screws 3.5 mm		-	Aluminium	Silver coloured anodized	2.5	402.30.642
					3.5	402.30.643
Double top running track, for screw fixing with countersunk head screws 3.5 mm, for door thickness 19 mm		-	Aluminium	Silver coloured anodized	2.5	402.30.652
					3.5	402.30.653
Single bottom guide track, with harpoon rib, for press fitting and glue fixing into groove 6 mm		-	Plastic	Grey	2.5	402.30.802
					3.5	402.30.803
Panel profile for glue fixing with adhesive strips		-	Aluminium	Silver coloured anodized	2.5	402.33.412
					3.5	402.33.413

Packing: 1 piece

Handles for sliding doors

► MB 10.233