



Häfele Slido D-Line43 80M Sliding door fitting














> Area of application: For private residential areas,

for 1-leaf sliding doors

for hard floors (laminate, PVC, tiles) and soft floors (carpet, cork - only for use in

combination with bottom track)

> Version: Invisible running equipment integrated in

door Door weight:

≤80 kg 800–1,800 mm Door width: > Adjustment facility: Distance door to wall +4 mm


(adjustment on both sides,


for compensating uneven walls),

height ±2 mm

> Installation: Wall mounting, floor must be even and level

Wall mounting





Floor guide on hard floors


Floor guide on soft floors with running track provided on site

A slight trace of wear may appear on the floor, depending on material. Tile gaps are noticeable when moving the door.

Installation reference

- > Make sure that floor is even and level
- Bottom track is required for soft floors
- > Prepare wall structure for top roller


Section running gear and floor guide



H = door height MH= installation height

H2 = internal opening height = internal opening width


Cut-out dimensions



Note

Please note the lateral door overlap with concealed installation according to drawing.

Door installation



Other mounting options can be found in the installation instructions.

12.01.2021 ID 2416

HAFELE

ightarrow Set with running track for 1 door

Model	Supplied with	Length mm	Cat. No.
80M	1 running track	1100	940.59.008
	1 running gear 2 soft and self closing mechanisms 1 guide track 1 floor guide 1 set of guide rollers 1 set of end caps (1 pair black, 1 pair silver coloured) 2 spacers 1 floor mounted stop (for optional use) 2 hex keys 1 open-ended spanner	1800	940.59.009

\rightarrow Tracks

	Material	Finish/colour	Length mm	Cat. No.
Bottom track for soft floors 30 x 4 mm (W x H)	Aluminium	Silver coloured anodized	2200	940.59.802
			3600	940.59.803
		Black anodized	2200	940.59.812
			3600	940.59.813