


→ Rotating, with stainless steel foot plate




- ① Hexagon socket SW5
- ② Square nut SW8

- > Material: Screw: Steel, glide: Plastic
- > Finish/colour: Screw: Galvanized, foot plate: Ground, glide: Black
- > Load bearing capacity: Approx. 250 kg/screw
- > Drive: Hexagon socket SW5 at top, square socket key SW8 at bottom

Thread length mm	Cat. No.
60	637.00.020

Packing: 1 or 25 pieces


→ Rotating, length 60–120 mm



- > Material: Steel
- > Finish: Galvanized
- > Load bearing capacity: Approx. 300 kg (static)
- > Drive: Hexagon socket SW4 or slot recess

Length L mm	Packing pieces	Drive Slot recess	Hexagon socket
60	1 or 200	637.02.009	637.03.009
70	1 or 200	637.02.018	637.03.018
80	1 or 100	637.02.027	637.03.027
90	1 or 100	637.02.036	–
100	1 or 200	637.02.045	637.03.045
120	1 or 150	637.02.054	637.03.054

Protective cap



- > Material: Plastic
- > Finish: Transparent

Installation	Cat. No.
For push-fitting onto foot plate	637.02.090

Packing: 1, 100 or 500 pieces




→ Fixing elements

With M10 internal thread




> Finish: Supporting bracket, double screw-on bracket and screw-on plate: Galvanized, T-nut and screw-in sleeve: Bright

Supporting bracket






	Cat. No.
Supporting bracket	637.30.980
Packing: 1 or 50 pieces	

Double screw-on bracket





	Cat. No.
Double screw-on bracket	637.07.004
Packing: 1 or 100 pieces	

Screw-on plate





Internal thread	Cat. No.
M8	651.14.900
M10	637.09.008
Packing: 1 or 100 pieces	

T-nut



	Cat. No.
T-nut	031.00.301
Packing: 100 or 500 pieces	

Screw-in sleeve



	Cat. No.
Screw-in sleeve	030.00.502
Packing: 100 or 500 pieces	