

A = 6 mm with 90° opening angle

· Area of application: For wooden frames,

for rebated wooden interior doors

Door weight: ≤40 kg Knuckle Ø: 15 mm


Drill bit Ø: Wing part 6.8 mm, frame part 7.2 mm

For use in combination with receiver

## Installation

6

Drill-In Hinges and Recessed Hinges



Material	Finish	DIN left	DIN right
Steel	Nickel plated	922.11.770	922.11.870


## Order reference

Following items are available on request: Mounting aid VARIANT V 0020/V 0026 WF series drilling jig.

Mounting aid VARIANT plastic drilling jig	►BB 6.58
Receiver for lining frames, screw-on pocket of VARIANT V 3610 series	►BB 6.41
Receiver for block frames and blind frames, VARIANT V 3604, V 3605 clamping block	►BB 6.41
Receiver for lining frames, block frames and blind frames, VARIANT V 3607 clamping block	►BB 6.42

For rebated doors up to 40 kg, for steel frames





A = 6 mm with 90° opening angle

Area of application:

For steel frames with VARIANT V 8600, V 8610 or V 8618 weld-on

pockets, for rebated wooden interior doors

Door weight: . ≤40 kg Knuckle Ø: 15 mm

Drill bit Ø: Wing part 6.8 mm

## Installation



Steel Nickel plated 922.23.571 922.23.671	Material	Finish	DIN left	DIN right
	Steel	Nickel plated	922.23.571	922.23.671

## Order reference

Following items are available on request: Mounting aid VARIANT V 0020/V 0026 WF series drilling jig.

Mounting aid VARIANT plastic drilling jig ►BB 6.58