



20 FB Door opening mechanism

For overlay or flush swing-out doors up to 20 kg




Application




Single door, (A) Internal cabinet width

Dimensions without brackets = internal cabinet width min. 398 mm Dimensions in brackets = internal cabinet width min. 475 mm



Corner solution with double doors


Dimensions without brackets = internal cabinet width min. 398 mm Dimensions in brackets = internal cabinet width min. 475 mm



A = Lateral door overlay B = Top and bottom door overlay

| > No offset, for use with internal pull outs or extending | |
|---|--|
| trays | |
| > With integrated soft closing mechanism | |


| > Area of application: | Door swings out to the front and to the side when being opened, allowing unlimited access to the cabinet interior, can be used for single doors, double doors with straight cabinet design and for corner solutions |
|----------------------------|--|
| > Internal cabinet width: | Min. 398 or 475 mm |
| > Internal cabinet height: | Max. 2,576 mm |
| > Adjustment facility: | +4 mm vertically, |
| . , | ±2 mm horizontally, |
| | ±4 mm tilting angle adjustment |
| > Material: | Zinc alloy |
| > Finish: | Powder coated silver coloured |
| | |



C Door opening mechanism, D Connecting bar

- E = Connecting bar length = H 76 mm =
- H 84 mm when using fixing set
- L = Internal cabinet width, H = Internal cabinet height

Drilling pattern



5

DGH-M 2021, HDE-en, 11/20; Dimensional data not binding. We reserve the right to alter specifications without notice.



CAD GAEB

5



Supplied with

1 Pair of door opening mechanisms

2 Door mounting brackets

| Version | Cabinet width mm | Max. door travel mm | Cat. No. |
|-------------------|------------------|---------------------|------------|
| With soft closing | Min. 398 | 450 | 407.32.906 |
| mechanism | Min. 475 | 600 | 407.32.907 |
| | | | |

Packing: 1 set

Order reference

Please order connecting bar and centre hinge separately.

\rightarrow Centre hinge




> Area of application: For stabilising the connecting bar with high doors

Note

Screws for connecting bar not supplied

| Material | Finish/colour | Cat. No. |
|----------------|--------------------------------|------------|
| Zinc alloy | Powder coated, silver coloured | 407.32.930 |
| Packing: 1 set | | |

\rightarrow Connecting bar, can be shortened



| Material | Finish/colour | Length mm | Cat. No. |
|-----------|-----------------|-----------|------------|
| Aluminium | Powder coated, | 1900 | 407.32.911 |
| | silver coloured | 2500 | 407.32.910 |

Packing: 1 piece

Note

instructions.


\rightarrow Cabinet fixing set



when using the cabinet fixing set.

Several dimensions change

Please observe installation



| > Area of application: | For fixing the fitting to top panels and base panels with heavy loads and high leverage force |
|------------------------|---|

| Material | Finish/colour | Cat. No. |
|------------------|--------------------------------|------------|
| Zinc alloy | Powder coated, silver coloured | 407.32.940 |
| Packing: 1 piece | | |