

**Ritterwerk AES 62 General-purpose slicer**  
For installation in drawer

Vitaflex




Picture shows AES 62 SR/SL,  
cutting right



- > Material: Housing: Aluminium alloy and plastic, sliding food carriage, residual holder and finger protection: Plastic, slice tray: Stainless steel, rustproof, blade: Stainless steel, rustproof
- > Finish: Housing: Metallic silver
- > Mains voltage: 230 V / 50 Hz
- > Wattage: 65 W
- > Version: With slice thickness adjustment from 0–14 mm, sliding food carriage, finger protection, residual holder, quick cut-out/permanent switch, slice tray, release button, fold-in blocking device with adjusted slice thickness, serrated blade Ø 170 mm
- > Weight: 4.1 kg
- > Short-term load: 5 min.
- > Cutting: Left or right
- > With operating and installation instructions



→ **AES 62 SR/SL**




- > For cabinet width: Min. 450 mm
- > Internal installation width: >344 mm
- > Dim.: 342 x 365 x 75 mm (W x D x H)
- > Installation: Distance from drawer base panel to top edge of worktop: Max. 161 mm



	Cat. No.
Cutting: Left	530.81.901
Cutting: Right	530.81.900

Packing: 1 piece

→ **AES 62 SR/SL-H**



For kitchens with handle profiles or thick worktops



- > For cabinet width: Min. 500 mm
- > Internal installation width: >392 mm
- > Dim.: 390 x 365 x 75 mm (W x D x H)
- > Installation: Distance from drawer base panel to top edge of worktop: 165–210 mm



	Cat. No.
Cutting: Left	530.81.941
Cutting: Right	530.81.940

Packing: 1 piece